



## HS1011 - Thermal Transfer Resin Ink for Fabric Applications

### Description

- White Thermal Transfer Resin Ink for Fabric Applications

### Printer Compatibility

- Avery Dennison Snap Series
- Avery Dennison 6xx
- Aftermarket Printers

### Applications

- Avery Dennison Coated Polyesters
- Avery Dennison Coated Nylons
- Avery Dennison Uncoated Polyester Satins (limited dry clean resistance – please test)

### Notes

Use HS1011 in combination with 4099IBT for harsh wash and production procedures where print durability is required.

HS1011  
Thermal Transfer  
Resin Ink for Fabric  
Applications



## HS1011: Technical Information

PRODUCT					
Product reference	HS1011				
Product type	Resin Ink				
Colour	White				
Product Status	Standard Product				
PROPERTIES					
Print technology	Thermal Transfer				
CSI/CSO	Ink In/Ink Out				
Carrier	Polyester film				
PROCESSING/COMPATIBILITY					
Performance: the recommended combinations are based on Avery Dennison's results and experience. It is essential that all fabrics and inks are thoroughly tested prior to use through your specific processes.					
Thermal printer compatibility	<ul style="list-style-type: none"> <li>Avery Dennison Snap Series</li> <li>Avery Dennison 6xx</li> <li>Aftermarket Printers</li> </ul>				
CONFIGURATION					
Put up	Code	Length	Core   CSI/CSO		
			P9	O1-CSI	O1-CSO
	HS1011	500	●		
	ODX2801	210			●
	ODX2801	250		●	
ODX2801	400			●	
<p> <b>P9</b> (AD 6xx/Snap Printers)  <b>O1-CSI</b>  <b>O1-CSO</b>  <b>Core</b>  <b>P9:</b> Plastic Paxar Core w/notches  <b>O1 - CSI:</b> Cardboard Core - Ink-in, Transparent Trailer  <b>O1 - CSO:</b> Cardboard Core - Ink-out, Silver Trailer         </p>					
Width tolerance	± 1 mm				
MISCELLANEOUS					
Shipping: Recommended shipping conditions for up to one month duration are -5°C to 45°C at 20% to 85% relative humidity. Storage: Suggested storage conditions for up to one year are -5°C to 45°C at 20% to 85% relative humidity.					
Oeko-Tex Class	In combination with Class 1 certificated substrates				
FMVSS	In combination with Flame retardant substrates				
Origin	Far East				
Similar Products	▲DC1181				

Products can be subject to change without notification. All information given is based on the results of testing performed by Avery Dennison. Customers should test any product thoroughly through all relevant processes.  
 © 2009 Avery Dennison. All rights reserved.

HS1011-V01-200902

### Information and Brand Management Division

#### Americas

7 Bishop Street  
 Framingham, MA 01702-8366  
 USA  
 Toll Free USA 800 545 9559  
 Int Tel +1 818 735 5000  
 Fax +1 818 735 6000

#### Europe, Middle East & Africa

Suite 24, Building 6  
 Hatters Lane  
 Croxley Green Business Park  
 Watford, Hertfordshire WD18 8YH  
 UK  
 Tel +44 (0) 1923 691000  
 Fax +44 (0) 1923 236967

#### South Asia

Plot No.94, Udyog Vihar Phase-I,  
 Gurgaon-122 016, Haryana,  
 India  
 Tel +91 124 4324 400  
 Fax +91 124 4324 500

#### Asia

32/F, Skyline Tower  
 39 Wang Kwong Road  
 Kowloon Bay, Kowloon,  
 Hong Kong  
 Tel +852 2400 4000  
 Fax +852 2785 1255